

www.hayikama.com



# ABOUT US



Our company entered the professional business world with hand weaving carpet production in early 70s and included carpet cleaning in its service range upon intense demands from the customers in 80s. Our company has visionary view point that provides identity to our institution. The fact that carpet cleaning costs were not economical in that period made us perform higher quality production in conformity with customer expectations, models with new technology were made.

HAYIKAMA started the production of the first machines in 2000s as a result of knowledge accumulation in the industrial production and carried its quality a step further. New machine models were designed and mass production started in order to increase the effeciency and reduce the cost of carpet cleaning.

HAYIKAMA is a company specialized in the manufacturing of industrial carpet cleaning systems. The company started its activities in 1970 by producing hand-knotted carpets then incorporated carpet washing services to its structure in 1980. The comapny invested in in the techology related the carpet cleaning systems in order to increase the quality production and reduce the carpet washing cost. Since 2005, HAYIKAMA started the manufacturing of new machines and increased the quality and efficiency of its cleaning systems by producing new machine models.

The company is working both domestically and internationally by exporting its machines to more than 48 countries around the world with a backround of 35 years experience. HAYIKAMA produces a full professional line for industrial carpet cleaning that regroups the following machines: Automatic dust remover, Automatic carpet washing machine, Automatic carpet spin dryer HAYIKAMA is also a solution partner and offers consultancy and training to its customers.

Our institution plays an active role in R&D works and is a leader in its sector and succeeded in being the symbol of quality for almost 45 years in gaining the trust of its customers.


# **OUR VALUES**

Hayıkama who provides service in its sector for many years believes in open and transparent communication in allbusiness processes from production to after sales service and the power ofempathetic approach in bilateral relations. Rooted past of our company is based on the following principles:

- -Customer satisfaction is more importantthan anything else. We listen to our customers and produce suitable andreasonable solutions suitable for their requirements which provide success and income in professional life.
- -We take pains to budgets in raw material purchasing in order to decrease our production costs and offer qualitywith most economical prices.
- -We follow new technologies closely and produce solutions that allow business developments and growths of our customers.
- -We believe that environmental awareness should increase for protecting natural resources which diminish gradually. Hayıkamatries to develop technical products that save water and energy.
- -As a company open for innovations wepay value to feedbacks from all our stake holders for continuous development. We realize those coinciding with our principles. We thank to all our partners whosupport our development.
- -We produce products which touch thefuture with cheery and experienced employees trained well.

# **AUTOMATIC CARPET WASHING MACHINE**

#### **E SERIES**



SPECIFICATIONS	HYM 284-E	HYM 335-E	HYM 435-E	
Max. Carpet Width	260 cm	420 cm		
Dimensions	330x225x170 cm	390x225x170 cm	490x225x170 cm	
Weight	1600 kg	1800 kg	2000 kg	
Washing Capacity	150 m²/h	180 m²/h	240 m²/h	
Number of Brushes	4 disc + moving scrapper + down roll brush	5 disc + moving scrapper + down roll brush		
Engine Power	9 kW 10 kW 10 kW			
Electricity		3 phase / 380 V / 50 Hz		
Button Control	✓			
Speed Control	✓			
Electronic Sensor System	✓			
Detergent Tank	✓			
Automatic Detergent Pump System	✓			
Carpet Trolley	✓			
Rolling System	$\checkmark$			



# **AUTOMATIC CARPET WASHING MACHINE**

#### **F SERIES**



SPECIFICATIONS	HYM 288-F	HYM 338-F	HYM 4310-F	
Max. Carpet Width	260 cm	420 cm		
Dimensions	380x410x240 cm	430x410x240 cm	530x410x240 cm	
Weight	3000 kg	3500 kg	4600 kg	
Washing Capacity	150 m²/h	240 m <sup>2</sup> /h		
Number of Brushes	8 disc + 2 combing brushes	8 disc + 2 combing brushes	10 disc + 2 combing brushes	
Engine Power	16,5 kW	20 kW		
Electricity		3 phase / 380 V / 50 Hz		
Touch Control Panel	✓			
Speed Control	$\checkmark$			
Electronic Sensor System	$\checkmark$			
Detergent Tank	✓			
Automatic Detergent Pump System	$\checkmark$			
Carpet Trolley	$\checkmark$			
Rolling System	$\checkmark$			



# **AUTOMATIC CARPET SPIN DRYER**

# (EXTRACTOR)



SPECIFICATIONS	HSS 265-40	HSS 320-40	HSS 320-47	HSS 420-47
Outer Drum	Painted			
Inner Drum	Stainless Steel			
Max. Carpet Width	265 cm	320 cm	320 cm	420 cm
Dimensions	110x320x135 cm	110x380x135 cm	120x395x150 cm	120x495x150 cm
Weight	600 kg	750 kg	1100 kg	1400 kg
Diameter of Inner Drum	40 cm	40 cm	47 cm	47 cm
Thickness of Inner Drum	3 mm	3 mm	4 mm	4 mm
Capacity	270 m <sup>2</sup> /h	360 m <sup>2</sup> /h	360 m <sup>2</sup> /h	480 m²/h
Engine Power	5,5 kW	7,5 kW	7,5 kW	11 kW
Maximum RPM	1300 rpm	1300 rpm	1000 rpm	1000 rpm
Voltage	3 phase / 380 V / 50 Hz			
Time Adjustment Working System		<b>~</b>	/	
Speed Control	×			
Suspension System	$\checkmark$			
Pneumatic Door Lock System	$\checkmark$			
Pneumatic Brake System	X			
Sensor System	×			



# **AUTOMATIC CARPET SPIN DRYER**


# PRO (EXTRACTOR)



SPECIFICATIONS	HSS 265-40 PRO	HSS 320-40 PRO	HSS 320-47 PRO	HSS 420-47 PRO
Outer Drum	Painted			
Inner Drum	Stainless Steel			
Max. Carpet Width	265 cm	320 cm	320 cm	420 cm
Dimensions	110x320x135 cm	110x380x135 cm	120x395x150 cm	120x495x150 cm
Weight	650 kg	800 kg	1200 kg	1500 kg
Diameter of Inner Drum	40 cm	40 cm	47 cm	47 cm
Thickness of Inner Drum	3 mm	3 mm	4 mm	4 mm
Capacity	270 m <sup>2</sup> /h	360 m <sup>2</sup> /h	360 m <sup>2</sup> /h	480 m <sup>2</sup> /h
Engine Power	5,5 kW	7,5 kW	7,5 kW	11 kW
Maximum RPM	1300 rpm	1300 rpm	1000 rpm	1000 rpm
Voltage		3 phase / 38	30 V / 50 Hz	
Time Adjustment Working System		·		
Speed Control	$\checkmark$			
Suspension System	$\checkmark$			
Pneumatic Door Lock System	$\checkmark$			
Pneumatic Brake System	$\checkmark$			
Sensor System	✓			




# **AUTOMATIC CARPET DUST REMOVER**



SPECIFICATIONS	HTM 250	HTM 350	HTM 450	
Chassis	Painted			
Max. Carpet Width	260 cm 320 cm		420 cm	
Dimensions	160x360x130 cm 160x420x130 cm		160x520x130 cm	
Weight	1200 kg 1450 kg		1900 kg	
Capacity	180 m <sup>2</sup> /h	240 m <sup>2</sup> /h	300 m <sup>2</sup> /h	
Motor Power	4,5 kW 4,5 kW 5,2 kW			
Vacuum Power	1800 m <sup>3</sup> /h 1800 m <sup>3</sup> /h 3500 m <sup>3</sup> /h			
Voltage	3 phase / 380 V / 50 Hz			
Rolling Mechanism	✓			
Speed Control	$\checkmark$			
Control Panel	✓			
Filter	$\checkmark$			



# **SWEEPING AND VACUUM MACHINE**



SPECIFICATIONS	HPM 250	HPM 350	HPM 450		
Chassis	Painted				
Band width	260 cm	260 cm 320 cm			
Dimensions	310x150x200 cm	370x150x200 cm	470x150x200 cm		
Weight	950 kg	1200 kg	1500 kg		
Sweeping Capacity	180 m²/h	240 m <sup>2</sup> /h	300 m <sup>2</sup> /h		
Number of Brush	1 roll brush	1 roll brush	1 roll brush		
Motor Power	4,5 kW	4,5 kW 4,5 kW 6 kW			
Vacuum Power	1800 m <sup>3</sup> /h 1800 m <sup>3</sup> /h 3500 m <sup>3</sup> /h				
Sub Cleaning Brush		Optional			
Voltage		3 phase / 380 V / 50 Hz			
Control Panel	✓				
Speed control	✓				
Vacuum system	✓				
Manual Rolling	$\checkmark$				



# **DEHUMIDIFIER**



- The ceiling of the drying rooms are calculated fully isolated (must be covered at least 4mm high dense styofoam including ceiling) with ceiling height of 2.30 meters.
- Channel thpe model (HKS Models) drying machines are mounted outside the drying room.
- Production of Air conditioning channels to be connected to drying machines and inside the room is not wihin the frame of the responsibility of our company.
- All our equipments work with three phase energy feding.

SPECIFICATIONS	HKS 350	HKS 450	HKS 600
Carpet Drying Capacity	350 m²	450 m <sup>2</sup>	600 m <sup>2</sup>
Drying Room Size	70 m <sup>3</sup>	100 m <sup>3</sup>	150 m <sup>3</sup>
Energy Consumption (hour)	5,5 kW	7,5 kW	8 kW
Amper	9 A	10,3 A	14.8 A
Maximum Humidity Removal Capacity	720 lt	800 lt	1120 lt
Operating Temperature Range	+5 -+55	+5 -+55	+5 -+55
Operating Humidity Range	%20 - %100	%20 - %100	%20 - %100
Phase / Voltage / Frequency	380 / 430	380 / 430	380 / 430
Weight	175 kg	185 kg	210 kg





- Minarelicavus Mah.105 (290) Sok. No:8/1 Nilufer/Bursa/TURKEY
- +90 224 411 0 356
- +90 224 411 1 013
- export@hayikama.com
- www.hayikama.com